



Tubi SS e FM



Gelmini Srl
Prodotti Siderurgici

TUBO "GAS" SENZA SALDATURA					
serie normale (nero e zincato)					
Diametri			spessore mm.	v.m. kg/m	liscio kg/m
D.N.	pollici	esterno mm.			
6	1/8"	10,2	1,80	0,372	0,369
8	1/4"	13,5	2,00	0,577	0,573
10	3/8"	17,2	2,00	0,753	0,747
15	1/2"	21,3	2,35	1,11	1,10
20	3/4"	26,9	2,35	1,42	1,41
25	1"	33,7	2,90	2,23	2,21
32	1 1/4"	42,4	2,90	2,87	2,84
40	1 1/2"	48,3	2,90	3,30	3,26
50	2"	60,3	3,25	4,63	4,56
70	2 1/2"	76,1	3,25	5,93	5,81
80	3"	88,9	3,65	7,82	7,65
100	4"	114,3	4,05	11,30	11,00
125	5"	139,7	4,85	16,70	16,20
150	6"	165,1	4,85	19,80	19,20
TUBO "GAS" SALDATO - DALMINE F.M. (FRETZ-MOON)					
serie leggera					
Diametri			spessore mm.	Nero liscio Peso kg/m	Zincato v.m. Peso kg/m
D.N.	pollici	esterno mm.			
10	3/8"	17,2	1,80	0,674	0,75
15	1/2"	21,3	2,00	0,952	1,04
20	3/4"	26,9	2,35	1,410	1,53
25	1"	33,7	2,65	2,010	2,16
32	1 1/4"	42,4	2,65	2,580	2,78
40	1 1/2"	48,3	2,90	3,250	3,48
50	2"	60,3	2,90	4,110	4,42
70	2 1/2"	76,1	3,25	5,800	6,22
80	3"	88,9	3,25	6,810	7,20
100	• 4"	114,3	3,65	9,890	10,20
125	• 5"	139,7	4,50	14,90	15,40

• Saldato tipo Fm